







**GASTRONOMIE
SI BRUTARIE
PROFESIONALA**



RX





RX SERIES

RX 203

Reference	710520
Internal dimensions	(W)360 x (D)290 x (H)260 mm.
External dimensions	(W)500 x (D)560 x (H)455 mm.
 Electric power	2.250 W
 Maximum temperature	250° C
 Weight	22 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	3x340x240 - 3xGN 1/2
Standard equipment	3 perforated aluminium trays
Humidifier Ref. 710521	
Safety thermostat - 0-60 Minute timer. Non-stop mode	







RX 304

Reference	710522
Internal dimensions	(W)450 x (D)340 x (H)345 mm.
External dimensions	(W)590 x (D)675 x (H)540 mm.
 Electric power	3.100 W
 Maximum temperature	250° C
 Weight	35 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x430x340 / 4 GN 2/3
Standard equipment	4 perforated aluminium trays
Humidifier Ref. 710523	
Safety thermostat - 0-60 Minute timer. Non-stop mode	







RX 424

Reference	710524
Internal dimensions	(W)500 x (D)410 x (H)350 mm.
External dimensions	(W)640 x (D)720 x (H)545 mm.
 Electric power	3.100 W
 Maximum temperature	250° C
 Weight	40 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x480x340 / 4 GN 2/3
Standard equipment	4 wire rack
Humidifier Ref. 710525	
End of cycle alarm - Safety thermostat - Chamber light 0-60 Minute timer. Non-stop mode	







RX SERIES

RX 603

Reference	710527
Internal dimensions	(W)680 x (D)470 x (H)285 mm.
External dimensions	(W)820 x (D)800 x (H)480 mm.
 Electric power	3.900 W
 Maximum temperature	250° C
 Weight	45 Kg.
 Voltage	230 V - 50/60 Hz
Connection	Single phase Schuko
Capacity	3x600x400 / 3 GN 1/1
Standard equipment	3 wire rack
Humidifier Ref. 710528	
End of cycle alarm - Door switch - Safety thermostat	
Rotation inverter - Chamber light - 0-60 Minute timer. Non-stop mode	







RX 604

Reference	710529
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	5.700 W
 Maximum temperature	250° C
 Weight	52 Kg.
 Voltage	400 V - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
Humidifier Ref. 710530	
Single phase modification option (230 V)	
End of cycle alarm - Door switch - Safety thermostat	
Rotation inverter - Chamber light - 0-60 Minute timer. Non-stop mode	







RX 604 Plus

Reference	710531
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	6.300 W
 Maximum temperature	250° C
 Weight	55 Kg.
 Voltage	400 V - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
Humidifier Ref. 710532	
Single phase modification option (230 V)	
End of cycle alarm - Door switch - Safety thermostat	
Rotation inverter - Chamber light - 0-60 Minute timer. Non-stop mode	







RX SERIES

RXL 304

Reference	710534
Internal dimensions	(W)450 x (D)340 x (H)345 mm.
External dimensions	(W)590 x (D)675 x (H)540 mm.
 Electric power	3.100 W
 Maximum temperature	250° C
 Weight	35 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x430x340 / 4 GN 2/3
Standard equipment	4 perforated aluminium trays
Humidifier Ref. 710535	
Change door opening	
Safety thermostat - 0-60 Minute timer. Non-stop mode.	







RXL 424

Reference	710536
Internal dimensions	(W)500 x (D)410 x (H)350 mm.
External dimensions	(W)640 x (D)720 x (H)545 mm.
 Electric power	3.100 W
 Maximum temperature	250° C
 Weight	40 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x480x340 / 4 GN 2/3
Standard equipment	4 wire rack
Humifier Ref. 710537	
Change door opening	
End of cycle alarm - Safety thermostat - Chamber light	
0-60 Minute timer. Non-stop mode	




RXL 603

Reference	710538
Internal dimensions	(W)680 x (D)470 x (H)285 mm.
External dimensions	(W)820 x (D)800 x (H)480 mm.
 Electric power	3.900 W
 Maximum temperature	250° C
 Weight	45 Kg.
 Voltage	230 V - 50/60 Hz
Connection	Single phase Schuko
Capacity	3x600x400 / 3 GN 1/1
Standard equipment	3 wire rack
Humidifier Ref. 710539	
Change door opening	
End of cycle alarm - Door switch - Safety thermostat	
Rotation inverter - Chamber light	
0-60 Minute timer. Non-stop mode	







RXL 604 Plus

Reference	710540
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	6.300 W
 Maximum temperature	250° C
 Weight	55 Kg.
 Voltage	400 - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
Humidifier Ref. 710530	
Single phase modification option (230 V)	
Change door opening	
End of cycle alarm - Door switch - Safety thermostat	
Rotation inverter - Chamber light	
0-60 Minute timer. Non-stop mode	



RX SERIES





RXD 384

Reference	710542
Internal dimensions	(W)450 x (D)370 x (H)345 mm.
External dimensions	(W)590 x (D)700 x (H)540 mm.
 Electric power	3.200 W
 Maximum temperature	260° C
 Weight	40 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x430x340 / 4 GN 2/3
Standard equipment	4 wire rack

Cooking phases - Recipe book - Door switch - Automatic preheating
3/4" Water connection - Safety thermostat - Chamber light
Rotation inverter



RXD 604 Plus





Reference	710543
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	6.300 W
 Maximum temperature	260° C
 Weight	55 Kg.
 Voltage	400 - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack

Single phase modification
option (230 V)

End of cycle alarm - 0 to 100% humidity regulation
Cooking phases - Recipe book - Door switch
Automatic preheating - 3/4" Water connection - Safety thermostat
Rotation inverter - Chamber light



RXDL 384

Reference	710544
Internal dimensions	(W)450 x (D)370 x (H)345 mm.
External dimensions	(W)590 x (D)700 x (H)540 mm.
 Electric power	3.100 W
 Maximum temperature	260° C
 Weight	40 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x480x340 / 4 GN 2/3
Standard equipment	4 wire rack
Change door opening	
End of cycle alarm - 0 to 100 % humidity regulation	
Cooking phases - Recipe book - Door switch	
Automatic preheating - 3/4" Water connection - Safety thermostat	
Chamber light - Rotation inverter	







RXDL 604 Plus

Reference	710545
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	6.300 W
 Maximum temperature	260° C
 Weight	55 Kg.
 Voltage	400 V - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
Single phase modification option (230 V)	
Change door opening	
End of cycle alarm - 0 to 100% humidity regulation	
Cooking phases - Recipe book - Door switch	
Automatic preheating - 3/4" Water connection	
Safety thermostat - Rotation inverter - Chamber light	







RX SERIES

RX 424 HG

Reference	710526
Internal dimensions	(W)500 x (D)410 x (H)350 mm.
External dimensions	(W)640 x (D)720 x (H)545 mm.
 Electric power	3.100 W
 Maximum temperature	250° C
 Weight	41 Kg.
 Voltage	230 V - 50 Hz
Connection	Single phase Schuko
Capacity	4x480x340 / 4 GN 2/3
Standard equipment	4 wire rack
Humidifier - Grill - End of cycle alarm - Safety thermostat Chamber light - 0-60 Minute timer. Non-stop mode	







RX 604 Plus HG

Reference	710533
Internal dimensions	(W)680 x (D)470 x (H)365 mm.
External dimensions	(W)820 x (D)800 x (H)560 mm.
 Electric power	6.300 W
 Maximum temperature	250° C
 Weight	56 Kg.
 Voltage	400 V - 50/60 Hz
Connection	Three phase 3F + N + T
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
Single phase modification option (230 V)	
Humidifier - Grill- End of cycle alarm - Door switch Safety thermostat - Rotation inverter Chamber light - 0-60 Minute timer. Non-stop mode	





RX SERIES

RXP 604

Reference	710546
Internal dimensions	(W)620 x (D)450 x (H)350 mm.
External dimensions	(W)760 x (D)760 x (H)545 mm.
 Electric power	3.800 W
 Maximum temperature	250° C
 Weight	52 Kg.
 Voltage	230 V - 50/60 Hz
Connection	Single phase
Capacity	4x600x400 / 4 GN 1/1
Standard equipment	4 wire rack
End of cycle alarm - Door switch - Safety thermostat	
Chamber light - 0-60 Minute timer. Non-stop mode	



ACCESSORIES

STANDS	DIMENSIONS	COMPATIBLE MODELS	RRP PRICE	
	RX 43/44 <i>Ref. 710547</i> (W)590 x (D)580 x (H)850 mm	RX 304 RXL 304		
	RX 48/34 <i>Ref. 710548</i> (W)625 x (D)640 x (H)850 mm	RX 424 RXL 424 RX 424 HG RXD 424 RXDL 424		
	RX 60/40 <i>Ref. 710549</i> (W)810 x (D)700 x (H)850 mm	RX 603 RXL 603 RX 604 RX 604 PLUS	RXL 604 PLUS RXD 604 PLUS RXDL 604 PLUS	
	RX GN 1/1 <i>Ref. 710550</i> (W)810 x (D)700 x (H)850 mm	RX 603 RXL 603 RX 604 RX 604 PLUS	RXL 604 PLUS RXD 604 PLUS RXDL 604 PLUS	
	<i>Ref. 710286</i>	Wheeled option		

FUMES CONDENSER KIT	DIMENSIONS	COMPATIBLE MODELS	RRP PRICE
	SERIE RX <i>Ref. 710551</i> (W)170 x (D)60 x (H)400 mm	SERIE RX	
	SERIE RX H20 <i>Ref. 710552</i> (W)720 x (D)85 x (H)450 mm	SERIE RX	
	SERIE RX DUO <i>Ref. 710553</i> (W)580 x (D)120 x (H)180 mm.	SERIE RX	

SUPERPOSITION KIT	DIMENSIONS	COMPATIBLE MODELS	RRP PRICE
	RX 43/34 <i>Ref. 710554</i> (W)590 x (D)675 x (H)40 mm.	RX 304 RXL 304	
	RX 48/34 <i>Ref. 710555</i> (W)640 x (D)720 x (H)40 mm.	RX 424 RXL 424 RX 424 HG	RXD 424 RXDL 424
	RX 60/40 <i>Ref. 710556</i> (W)820 x (D)800 x (H)40 mm.	RX 603 RXL 603 RX 604	RX 604 PLUS RXL 604 PLUS RXD 604 PLUS RXDL 604 PLUS